PATENT ABSTRACTS OF JAPAN

(11) Publication number:

10248844 A

(43) Date of publication of application: 22.09.1998

(51) Int. CI

A61B 8/00

(21) Application number:

09058113

(22) Date of filing:

12.03.1997

(54) ULTRASONIC IMAGE DIAGNOSTIC DEVICE

(57) Abstract:

PROBLEM TO BE SOLVED: To provide an ultrasonic image diagnostic device capable of eliminating the distortion of a three-dimensional image and displaying a correct image by obtaining image data without narrowing a viewing field for ultrasonic tomograms and causing rotation of images even if the images are moved.

SOLUTION: An ultrasonic image diagnostic device, having an ultrasonic probe 1 whereby threedimensional image data consisting of a plurality of successive ultrasonic tomograms is obtained, is provided with a rotation means (polar coordinate converting part 28) which rotates the first ultrasonic tomogram involved in the plurality of ultrasonic tomograms and a correlation computing means (correlation computing part 28) which outputs a correlation value by comput(71) Applicant: OLYMPUS OPTICAL CO LTD

ing the correlation between the first ultrasonic tomogram rotated by the rotation means and the second ultrasonic tomogram involved in the plurality of ultrasonic tomograms, the rotation means re-rotating the first ultrasonic tomogram at an angle at which the correlation value computed by the correlation computing means is

KAWASHIMA TOMONAO

highest.

(72) Inventor:

COPYRIGHT: (C)1998,JPO

